

POWER KLEEN DEFOAMER S

Parts Washing System Defoamer

A Concentrated High Performance silicone defoamer tailored specifically to suppress foam in aqueous parts cleaning solutions. The ultimate antifoam for use in MART Power Washer machines and jet spray washers that can tolerate silicone.

- Extremely effective in controlling foam at very low use levels of parts per million.
- Allows long wash cycles without interference from foam buildup.
- Defoams at all wash temperatures from 120°F to 212°F.
- Is effective in oil laden and detergent laden parts cleaning baths.
- Effective over a wide range of pH up to highly alkaline pH 14.
- Does not cause a loss in cleaning performance.
- Does not build-up or clog piping washing machines.
- Water-soluble

Use Instructions

The amount of Defoamer "S" required is dependent on the particular application. The primary factors are the surface area of the water, and the nature of the foam causing ingredients.

Defoamer S is generally effective at a level of 0.01% to 0.2 % of the system wash solution. In a typical 180 to 450 gallon washing machine it can be added a half cup at a time while the machine is running until the desired foam control is achieved. (Allow a short period of time between additions for the defoamer to disperse before adding additional amounts.)

Defoamer S is a temperature, independent defoamer and controls foam at any operating temperature.

Technical Data

Form	Viscous Liquid
Color	Milky
pH (as is)	Essentially Neutral
Stability.....	Excellent

**For Use Precautions and First Aid Information, please see the Material Safety Data Sheet.
Medical Emergency Hotline 1-800-246-2890**



2450 Adie Road Suite 100 ▼ Maryland Heights, MO 63043
Telephone: 314-567-3705 ▼ Fax: 314-567-6318 ▼ www.marttechservices.com