

Power-Kleen RI

Rust Inhibitor

Corrosion Protection for Steel & Iron Parts

GENERAL DESCRIPTION

Power-Kleen RI Rust Inhibitor is a concentrated parts rinsing chemical for flash rusting and corrosion protection of Steel, Iron, and Yellow Metal Parts. Power Kleen RI is a liquid that is injected into the rinse water. Highly effective with all Power-Kleen detergents.

ADVANTAGES

- Protects parts from flash rusting immediately after drying
- Provide short-term corrosion protection for storage
- Concentrated for low usage and cost
- No silicone to cause paint adhesion or fish eye problems
- Does not require premixing
- Low odor and does not cause staining
- Does not inhibit or interfere with the cleaning process. Doesn't affect the cleaning chemical, No reduction in Cleaning power of your chemistry



APPLICATION GUIDELINES

Power-Kleen Rust Inhibitor is designed for use at extremely low quantities:

- Mix ratio: .5 oz to 1 oz per gallon.
- Temperature 150 to 210°F. Recommend as hot as possible.

PHYSICAL PROPERTIES (TYPICAL DATA)

Form.....Liquid
Color (concentrate)Yellow
Odor.....Mild

pH range of Working Solution.....11.5
pH of concentrate.....Neutral



2450 Adie Road, Maryland Heights, MO 63043 USA
Ph 800-543-6278 Fax 314-567-6318
E-mail service@stingwash.com Website www.stingrayservice.com

MIXING INSTRUCTIONS

The recommended use for StingRay / MART Parts Washers, heat the water to at least 160 degrees. Rust inhibitor may be added to the rinse through the chemical injector pump by placing the pump feed tube into the Rust inhibit or container. Make sure the amount of chemical metered into the rinse does not exceed 2/3 oz per gallon of water in reservoir. This chemical may also be sprayed on to the part after washing. Avoid contact with chemical and solution. Avoid inhaling dust and fumes. Operate the wash cycle at 160 to 190 degrees F. Instructions can also be found on the Power-Kleen Rust Inhibitor label, MTS Website or reference the StingRay/MART Parts Washer Operating Manual for mixing in the washer.

HEALTH AND SAFETY

Get the most recent MSDS from our website at www.stingrayservice.com. or call StingRay Tech Services

NOTES:

Part Number	Package Size
52837	5 gal Pail
52838	55 gal Drum

- Shipping: UPS Ground or LTL Truck
- For additional information, please contact:

StingRay Tech Services at 1-800-543-6278 or visit our Website: www.stingrayservice.com

RUST INHIBITOR INJECTOR PUMP SYSTEM:

The Rust Inhibitor Injection Pump for using Power Kleen RI is available on all StingRay / MART Parts Washers. This system is easily added to any StingRay / MART Washer in the field. Call for details

