

Solution Transfer Pump Cart

High Capacity Water Extractor

The solution transfer pump cart system is especially designed for transferring water-based liquids, fluids and solutions. The portable unit is ideal for transferring liquids between washer reservoirs, holding tanks, drums and sumps. The rubber tire wheels of the pump cart allow easy moving of the unit throughout your facility.

This portable transfer pump features:

- **Transfers up to 180 gallons per minute (GPM)**
- Self Priming Centrifugal Pump offers flexibility, economy and simplicity.
- Cast iron pump housing for long life
- Engineered cast-iron impeller designed for durability.
- 115 volt, 1/2 Horse Power motor.
- Permanently lubricated ball bearings.
- Carbon ceramic shaft seal.
- 12' heavy-duty power cord with on/off switch.
- Operating Temperature range of: 40° F to 158° F (5° C to 70°C).
- Dependable self-priming pump handles high-volume industrial liquids and chemical transfer.
- Heavy-Duty All Steel Hand Truck with cushioned no-flat Rubber-Tread wheels for easy movement to site.



Vertical Lift Feet	GPM
2	180
5	80
10	53
20	49
30	45

- Smooth-Bore Flexible PVC transfer hoses for unrestricted flow and easy cleaning.
- Quick disconnect fittings on suction and discharge hoses. 10 foot suction hose and 20 foot discharge hose length.
- Stainless steel #40 mesh Suction strainer prevents solids from entering pump.
- Chemically resistant to most alkalis. Not for flammables.